

[AQUA ENERGY INTERNATIONAL](http://www.aquaenergy.com)

**8 St James Business Centre
Linwood Road, Paisley PA3 3DW
Scotland, UK
Tel: (+44) (0) 141 849 6888
Fax: (+44) (0) 141 848 5777
E-mail: info@aquaenergy.com
<http://www.aquaenergy.com>**



MODEL “DT-7250” HIGH PRESSURE WATER JETTING UNIT.

Trailer Mounted for manoeuvrability.

- MODEL** : “DTI-7250, 20 to 55 horsepower High Pressure Water Jetting Unit.
- PERFORMANCE** : 7,250 psi @ 7.89 gpm (500 bar @ 30.00 l/min) other performances available.
- PUMP** : JL-18, three cylinder triplex pump with safety rupture disc.
- ENGINE** : ISUZU water cooled engine, optional choice of Perkins, Kubota or Hatz Silenced engines.
- CONTROLS** : Three-way selector valve, pressure gauge, oil pressure indication, 12volt start.
- TRAILER** : Pump and engine mounted on sub-frame with flexible mounts to road trailer. Twin 13” wheels, auto reverse over-run Brakes, 50mm tow hitch, full road lights to EEC regulations.
- HOSE REEL** : 300’feet (91mts) capacity manual or hydraulic hose reel with in-out control.
- HOSES** : Safety Leader Hose, Drain and Sewer, Heat Exchanger, Flexible Lances.
- ACCESSORIES** : Wide assortment of Pipe and Sewer jets, control Guns, Surface Preparation Nozzles, Abrasive Blast Nozzles, Patented Shape Jets. Foot Control Valves.

Aqua Energy can design our products to the clients specification, using the very latest CAD systems. For further information contact the above address or visit our World Wide Web Site:

<http://www.aquaenergy.com>

Standard Features

Pump- JL-18 horizontal triplex positive displacement pump. JL-18 rated up to 45HP service. Plunger pump consists of chemical nickel-treated cast iron head. Stainless steel valves, seats, springs and stainless steel plungers with ceramic coating. The plungers and packing are water lubricated. The power end of the JL-18 pump is positive splash oil lubricated with sight glass for oil level check. Crankshaft is gas nitrated, hardened and tempered alloy steel. Main bearings are roller.

Suction Plumbing- 1" FBSP inlet port.
Twin easy clean water filters ensures a clean water supply to the pump.

Discharge Plumbing- Discharge manifold with ½" FBSP outlet port.
Glycerine filled pressure gauge and safety rupture disc.

Unit Mounting- Mounted on a steel channel frame with pump base and adjustable motor base. Steel plate top deck.

Power Transmission- Pump and engine connected via non-slip belt drive and safety guard.

Finish System- Units are zinc primed and have one coat of industrial blue (or choice of colour) enamel. Coating for corrosive atmospheres are available.

Optional Accessories:

Gun- Hand or foot dump control type with safety shroud, whip hose and coupling.

Hoses- Ultra high pressure for use at pressures up to 20,000 psi.

Lances- Rigid and flexible variety SAE, JIC, pipe and welded end connections.

Nozzles- Wide assortment for surface and tube cleaning.

Regulator- Variable flow and pressure adjustment. Controlled by hand or mechanical actuation.

Auto-Throttle- Variable engine speed adjustments with automatic return to idle when Dyna-Gun is depressurised.

Vacuum- Uses the Jet-Blaster pump to create a vacuum for sludge and slurry transport.

Line Mole- Pipe and sewer cleaning type with replaceable fan and round jet inserts.

Abrasive Injector- Dyna-Saw abrasive injector mixes abrasive into Dyna-Gun discharge stream.

Deck Cleaner- Rotary jet driven multi-nozzle floor and grate cleaning system with hand operated controls.

Couplings- Quick disconnect Acme thread rated at up to 20,000 psi working pressure. Optional snap type for use to 10,000 psi.

For further information contact: Aqua Energy International Limited
8 St James Business Centre
Linwood Road, Paisley PA3 3AT
Scotland, UK
Tel: (+44) (0) 141 849 6888
Fax: (+44) (0) 141 848 5777
E-mail: info@aquaenergy.com
<http://www.aquaenergy.com>