

AQUA ENERGY

**Electric Driven
Skid & Trolley Mounted
High Pressure Water Jetting Units**
Choice of Sound Attenuated Canopies & Offshore Crash-Frames
All models conform to CE Regulations

Model: ES-40-BS



PERFORMANCE

500 bar @ 30.00 l/min
400 bar @ 37.00 l/min
320 bar @ 45.00 l/min
250 bar @ 59.00 l/min
180 bar @ 62.00 l/min

Model: ET-50

PERFORMANCE

7,250 psi @ 07.90 gpm
5,800 psi @ 09.80 gpm
4,650 psi @ 11.90 gpm
3,600 psi @ 15.90 gpm
2,600 psi @ 16.30 gpm



**Aqua Energy International, St James Business Centre, Linwood Road,
Paisley PA3 3AT, Scotland, UK**

Tel: (+44) (0) 141 849 6888 Fax: (+44) (0) 141 848 5777

E-mail: info@aquaenergy.com www.aquaenergy.com

Standard Features

Pump- ES-ET 40/50 horizontal triplex positive displacement pump, rated up to 50 HP service. Plunger pump consists of stainless steel fluid cylinders, solid ceramic plungers, stainless steel valves and seats with chevron packing. The plungers and packing are water lubricated. The power end of the **ES-ET 40/50** series pump is positive splash oil lubricated with sight glass for oil level check.

Crankshaft
is made of high strength alloy steel. Main bearing is roller.

Suction Plumbing- Water filter 5 TO 300 micron capacity protects pump.
50 to 200 gallon water storage tank with ball cock and float.

Discharge Plumbing- Discharge manifold with interchangeable high pressure discharge connections for pressure gauge, relief valve, rupture disc and hose couplings. Stainless steel glycerine filled pressure gauge, stainless steel snubber assembly, Rupture disc or relief valve.

Unit Mounting- Mounted on a steel channel frame with pump base and anti-vibration mountings. Steel plate top deck and offshore crash frame.

Power Transmission- Direct Drive via a reduction gearbox or belt drive.

Finish System- Units are zinc primed and have one coat of industrial blue (or choice of colour) enamel. Coatings for offshore corrosive atmospheres are available.

Optional Accessories:

Dump-Gun Hand or foot dump control type with safety shroud, whip hose and coupling.

Hoses- High Pressure for use at pressures up to 40,000 psi.

Lances- Rigid and flexible variety SAE, JIC, pipe and welded end connections.

Nozzles- Wide assortment for surface and tube cleaning.

Rotary- Surface Preparation Jet for coatings removal and descaling

Regulator- Variable flow and pressure adjustment. Controlled by hand or mechanical actuation.

Auto-Throttle- Variable engine speed adjustments with automatic return to idle when Aqua-Gun is depressurised.

Vacuum- Uses the Jet-Blaster pump to create a vacuum for sludge and slurry transport.

Line Mole- Pipe and sewer cleaning type with replaceable fan and round jet inserts.

Abrasive Injector- Aqua-Saw abrasive injector mixes abrasive into Aqua-Gun discharge stream.

Deck Cleaner- Rotary jet driven multi-nozzle floor and grate cleaning system with hand operated controls.

Couplings- Rated at up to 40,000-psi (2,758 bar) working pressure. Optional snap type for use to 10,000 psi.

For further information contact: Aqua Energy International Limited
St James Business Centre
Linwood Road,
Paisley PA3 3AT, Scotland UK
Tel: (+44) (0) 141 849 6888
Fax: (+44) (0) 141 848 5777
E-mail: info@aquaenergy.com
www.aquaenergy.com